

EVEREST® 100 Synthetic Refrigeration Lubricant

DESCRIPTION

EVEREST® 100 is a formulated ISO 100 grade synthetic polyol ester refrigeration lubricant compatible with HFC refrigerants, including R-134a, R-404A, R-407C and R-410A.

FEATURES & BENEFITS:

- Compatible with HCFC & HFC refrigerants
- Suitable for use with R-134a, R-404A, R-407C, R410A and R-22 retrofit blends such as R 422D and R-427

APPLICATIONS:

Reciprocating, rotary, scroll, centrifugal/screw refrigeration compressors

SPECIFICATION PROPERTIES OF EVEREST® 100

PROPERTY	SPECIFICATIONS	METHOD
Appearance	Bright and Clear Liquid	Visual
Kinematic Viscosity @ 100 °C, cSt	9.5 - 11.6	ASTM D-445
@ 40 °C, cSt	90.0 - 105.0	ASTM D-445
Pour Point, °C	- 30 max	ASTM D-5950
Density @ 15.6°C, lbs.∕gal	8.00 - 8.10	ASTM D-4052
Total Acid Number, mg KOH/g	0.10 max	ASTM D-974 mod
Water, ppm	50 max	ASTM D-1533
ASTM Color	0.5 max	ASTM D-1500





TYPICAL PROPERTIES OF EVEREST® 100

PROPERTY	TYPICAL INSPECTIONS	METHOD
Kinematic Viscosity @ 100 °C, cSt	10.6	ASTM D-445
@ 40 °C, cSt	95.7	ASTM D-445
Viscosity Index	93	ASTM D-2270
Total Acid Number, mg KOH/g	0.02	ASTM D-974 mod
Flash Point, °C	271	ASTM D-92
Pour Point, °C	-34	ASTM D-5950
Specific Gravity, 15.6 °C/15.6 °C	0.967	ASTM D-4052
Density @ 15.6 °C, lbs/gal	8.05	ASTM D-4052
Water, ppm	25	ASTM D-1533
Low Temperature Miscibility Limit (10 Vol % lubricant in refrigerant, °C)		Sealed Tube
R-134a	-35	
R-404A	-60	
R-407C	-19	
R-410A	-19	

Technical Information Effective: 26 May 2016





A company of the LANXESS Group

The information contained herein relates to a specific Chemtura product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCTS CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the

The Chemtura logo is a trademark of Chemtura Corporation or one of its subsidiaries.

Copyright © 2016 Chemtura Corporation. All rights reserved.

North America

+1.800.325.6252 customer.care@chemtura.com

Europe, Middle East & Africa

+44.161.875.3800 emea.export@chemtura.com

South & Central America

+55.19.3522.5000 Atendimento.cliente@chemtura.com

Asia Pacific

+86.21.3866.6509 orders.apac@chemtura.com

Page 3 of 3

Technical Information Effective: 26 May 2016

