

EVEREST® 22

Synthetic Refrigeration Lubricant

DESCRIPTION

EVEREST® 22 is a formulated ISO 22 grade synthetic polyol ester refrigeration lubricant compatible with HFC refrigerants, including R-134a, R-404A, R-407C and R-410A.

FEATURES & BENEFITS:

- Compatible with HCFC & HFC refrigerants
- Suitable for use with R-134a, R-404A, R-407C, R-410A and R-22 retrofit blends such as R-422A, R-422D and R 427

APPLICATIONS:

Reciprocating, rotary and scroll refrigeration compressors.

SPECIFICATION PROPERTIES OF EVEREST® 22

PROPERTY	SPECIFICATIONS	METHOD
Appearance	Bright and Clear Liquid	Visual
Kinematic Viscosity @ 100 °C, cSt	4.4 - 4.9	ASTM D-445
@ 40 °C, cSt	20.5 - 24.2	ASTM D-445
Pour Point, °C	-57 max	ASTM D-5950
Density @ 15.6°C, lbs./gal	8.22 - 8.32	ASTM D-4052
Total Acid Number, mg KOH/g	0.10 max	ASTM D-974 mod
Water, ppm	50 max	ASTM D-1533
ASTM Color	0.5 max	ASTM D-1500



TYPICAL PROPERTIES OF EVEREST® 22

PROPERTY	TYPICAL INSPECTIONS	METHOD
Kinematic Viscosity @ 100 °C, cSt	4.7	ASTM D-445
@ 40 °C, cSt	23.5	ASTM D-445
Viscosity Index	120	ASTM D-2270
Total Acid Number, mg KOH/g	0.02	ASTM D-974 mod
Flash Point, °C	252	ASTM D-92
Pour Point, °C	-59	ASTM D-5950
Specific Gravity, 15.6 °C/15.6 °C	0.993	ASTM D-4052
Density @ 15.6 °C, lbs/gal	8.27	ASTM D-4052
Water, ppm	25	ASTM D-1533
Low Temperature Miscibility Limit (10 Vol % lubricant in refrigerant, °C)		Sealed Tube
R-134a	< -50	
R-404A	< -60	
R-407C	< -35	
R-410A	< -40	



A company of the
LANXESS
Group

The information contained herein relates to a specific Chemtura product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCTS CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.

The Chemtura logo is a trademark of Chemtura Corporation or one of its subsidiaries.

Copyright © 2016 Chemtura Corporation. All rights reserved.

North America

+1.800.325.6252
customer.care@chemtura.com

Europe, Middle East & Africa

+44.161.875.3800
emea.export@chemtura.com

South & Central America

+55.19.3522.5000
Atendimento.cliente@chemtura.com

Asia Pacific

+86.21.3866.6509
orders.apac@chemtura.com

