

## **Petadd PPD(C)**

### **Polymethacrylate Pour Point Depressant**

#### **Description**

Petadd PPD(C) is a polymethacrylate type pour point depressant (PPD). This product is typically used as a PPD in transmission lubricants and in crankcase formulations where Group II/III base stocks are used.

#### **Application**

- The recommended treat rate is between 0.05% and 0.5%, depending on the base stock used and the required pouring point (°C).

#### **Typical Properties**

<b>Property</b>	<b>Typical</b>	<b>Min.</b>	<b>Max.</b>	<b>Method</b>
Appearance	Clear Liquid	-	-	Visual
Colour	-	-	3.0	ASTM D1500
Density @15°C (kg/m <sup>3</sup> )	905	-	-	ASTM D4052
K.V. @100°C (mm <sup>2</sup> /s)	-	380	625	ASTM D445
Flash Point (PMCC, °C)	-	100	-	ASTM D93
Pour Point (@ 0.2% treat, °C)	-	-	-15	ASTM D97
Oil Content (%m)	-	-	50	Internal

#### **Storage and Handling**

Store at ambient temperature, sealed in the original containers and protected from moisture. Shelf life: 24 months. The maximum recommended temperature for handling and unloading is 60°C. Consult the SDS for further information.

*The information contained within this publication is based on the present state of our knowledge. Any recommendations or conclusions are made without liability on our part. Values shown are typical and should not be construed as specification limits.*