

Petfuel D-ULS MP

Multifunctional Package for Diesel Fuels

Description

Petfuel D-ULS MP is a multifunctional package designed to comply with the most recent EEC regulations for the treatment of Low Sulphur Diesel fuels, and fuels from different sources such as biofuels.

This product is a highly stable mix of additives that will minimise- engine deposits, corrosion, and foaming. This Petfuel product also improves Lubricity, Cetane Index Number, and clarity (through dehazing additives).

Application

- Use in Low Sulphur Diesel fuels to protect from wear & corrosion, and boost overall performance, whilst improving the emissions profile.
- Compatible with most aromatic and aliphatic hydrocarbon solvents.
- Recommended treat rates 200-700ppm, depending on the performance level required.

Typical Properties

Property	Typical	Min.	Max.
Active Content (%wt)	100	-	-
Viscosity @20°C (cSt)	-	-	10
Viscosity @40°C (cSt)	-	-	6
Density @15.6°C (g/cm ³)	0.95	-	-
Specific Gravity @20°C (g/cm ³)	-	0.92	0.98
Flash Point (PMCC, °C)	-	61	-
Pour Point (°C)	-	-	-30

Storage and Handling

Observe good chemical handling and hygiene practice. In-house assessment of the compatibility of this product with other additives is recommended. Consult the SDS for further information.

The information contained within this publication is based on the present state of our knowledge. Any recommendations or conclusions are made without liability on our part. Values shown are typical and should not be construed as specification limits.