

Petfuel D MP

Diesel Fuel Performance Package

Description

Petfuel D MP is a multipurpose additive package, designed to improve the quality of B30 diesel fuels. It prevents the accumulation of injector deposits in both direct and indirect injector engines, while also boosting the cetane number and improving overall stability through antioxidant action. This product has excellent water separability, and also helps reduce and control foam levels.

Application

- Use in B30 diesel fuels to protect from corrosion and deposit formation.
- Use in B30 diesel fuels to improve the cetane number and stability.
- Improves fuel efficiency and improves the emissions profile.
- Insoluble in water; soluble in aliphatic and aromatic solvents.
- Recommended treat rate ~600ppm (mg/L)

Typical Properties

Property	Typical	Min.	Max.
Appearance	Clear amber liquid	-	-
Density @15°C (g/cm ³)	0.95	-	-
Flash Point (°C)	-	62	-
Viscosity @20°C (mm ² /s)	6.4	-	-
Viscosity @40°C (mm ² /c)	3.8	-	-
Pour Point (°C)	-	-	-35

Storage and Handling

Observe good chemical handling and hygiene practices. Do not store at temperatures >40°C. Avoid contact with rubbers, polyethylene, polystyrene and polypropylene. This product has a shelf life of 12 months, if stored and used as prescribed.

The information contained within this publication is based on the present state of our knowledge. Any recommendations or conclusions are made without liability on our part. Values shown are typical and should not be construed as specification limits.