

## **Suretech AF-F6**

### Silicone antifoam for fuels

#### **Description**

Suretech AF-F6 is a silicone containing antifoam designed for use in fuels and distillation processes. This product demonstrates good spread power and has a low surface tension, making it extremely well suited for use in non-aqueous systems. It is widely compatible with aliphatic or aromatic hydrocarbon solvents.

#### **Application**

- Recommended treat rate of 4-20 ppm.
- Suitable for applications including diesel fuels products, crude-oil degassing, and distillation processes.

#### **Typical Properties**

Property	Typical	Min.
Silicone Content (%wt)	6.00	-
Viscosity @40°C (cSt)	6.0	-
Specific Gravity @16°C (g/cm <sup>3</sup> )	0.95	-
Density @20°C (kg/m <sup>3</sup> )	950	910
Flash Point (°C, PMCC)	-	61
Pour Point (°C)	-30	-

#### **Storage and Handling**

Store at 0-40°C in the original, unopened container, and in a dry & well-ventilated place. Keep away from foodstuffs. Observe good chemical hygiene and handling practice. If handled and stored correctly, this product has a shelf life of 12 months. For further information, please consult the SDS.

*The information contained within this publication is based on the present state of our knowledge. Any recommendations or conclusions are made without liability on our part. Values shown are typical and should not be construed as specification limits.*